

REYNOLDS**PivotDUMP. Carry All SCRAPERS**

Applications: General Earthmoving, Landforming, LASER cut and fill operations in Construction, Mining and Agriculture.
Features: Hydraulic cutting height control, pivoting bucket and sequenced front gate opening.
 Cutting edge moves/pivots with the bucket. Standard rear hitch and hydraulic outlets for second unit.



model	heaped capacity		cutting width		transport width		tires	shipping weight		Tractor
	cu. yd.	m3	inch	meter	inch	meter	(qty) size	lbs.	Kg	HP req'd
18 CS 14	18.0	13,7	168	4,26	187	4,75	(6) 17.5 x 25	17,000	7727	350-450
18 CMX 12.5	18.0	13,7	150	3,81	167	4,24	(4) 20.5 x 25	21,000	9545	400-450
17 CS 12	17.0	13	144	3,65	163	4,14	(4) 20.5 x 25	18,000	8192	350-400
17 CS 12 LGP	17.0	13	144	3,65	163	4,14	(2) 66 x 43-25	18,400	8364	350-400
17 C 12	17.0	13	144	3,65	163	4,14	(4) 20.5 x 25	17,500	7955	350-400
17 C 12 LGP	17.0	13	144	3,65	163	4,14	(2) 66 x 43-25	17,900	8136	350-400
16 CS 10	16.0	12,2	120	3,05	137	3,48	(4) 20.5 x 25	17,000	7727	300-350
16 CS 10 LGP	16.0	12,2	120	3,05	137	3,48	(2) 66 x 43-25	17,400	7907	300-350
14 CS 10 LGP	14.0	10,6	120	3,05	137	3,48	(2) 66 x 43-25	14,000	6364	250-300
14 CS 10	14.0	10,6	120	3,05	137	3,48	(4) 20.5 x 25	13,600	6182	250-300
12 C 10	12.0	9,1	120	3,05	137	3,48	(4) 17.5 x 25	12,500	5680	180-230
10 C 7	10.0	7,6	84	2,13	103	2,62	(4) 13.00x24	8,000	3636	150-200
8 C 7	8.0	6,1	84	2,13	99	2,52	(4) 13.5x16.1	6,800	3090	130-180

Low Ground Pressure TIRE 66x43-25 (LGP)**20.5 x 25 TIRE**

REYNOLDS SCRAPERS, L.L.C • P.O. BOX 2608 • SEGUIN, TX 78156 • USA

Tel. (210) 240-8220 • Fax (956) 687-3082 • www.reynoldsinternational.com

Email: info@reynoldsinternational.com